



# ZOFFANY

## TRUE MATT

### DESCRIPTION

Fast drying, fabulously flat and environmentally friendly, Zoffany True Matt is a water based emulsion that combines irresistible chalky looks with a wipeable finish.

Perfect for walls and ceilings, this transformative paint is quick drying, enveloping interiors in Zoffany's signature style. Visible brush strokes and cutting in are reduced and intense pigments provide an incredible depth of colour.

### KEY PROPERTIES

- Dries flat in two hours, leaving a luxurious, high performance finish
- Wipeable and environmentally friendly
- Excellent scrub resistance and good resistance to marring for its sheen level
- Ideal for high traffic areas such as hallways and kitchens

### PREPARATION

All surfaces should be sound, clean, dry and free from grease. Remove any loose or flaking paint. Rub down sound glossy surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a pre-coat of a water/acrylic primer undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960's paint surfaces as they may contain harmful lead. Prime base surfaces with an appropriate primer.

### APPLICATION

Stir well before use and apply by brush or roller. When using a roller, use a medium pile synthetic type. Do not overfill the tray. Ensure roller is loaded evenly. If using a brush, load generously. Apply liberally and evenly; avoid overspreading.

### CLEANING

Remove as much product as possible from equipment before cleaning. Clean immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty waste paint into drains or watercourses.

### HEALTH & SAFETY

- Contains a reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.

- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or white spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. Safety data sheet available on request.

### RECOMMENDED USES

Suitable for commercial and residential spaces.

### TYPE OF SUBSTRATE

Interior walls and ceilings.

### COLOUR RANGE

Alchemy of Colour collection, 156 colours.

### FINISH

Minimal sheen.

### VOLUME SOLID

35%

### COVERAGE

One coat of Zoffany True Matt covers up to 15m<sup>2</sup> per litre, depending on the nature and porosity of the surface.

### DRYING TIME

Touch dry in 1 - 2 hours. Recoatable after 2 - 4 hours.

### TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position.

### CLEANER

Clean water.

### VOC CONTENT

- Minimal VOC Content <0.29%
- VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.
- EU limit value for this product (Cat A/a): 30g/l (2010).
- This product contains max 2g/l VOC.

### FILM THICKNESS

Wet: 100µm, Dry: 48µm

### SIZES

2.5 Litre, 5 Litre